

Karima tömítés méretek

Anyagminőség tulajdonságok a **táblatömítés** pontban részletezve

DN (mm)	ID	OD					
		PN 2.5	PN 6	PN 10	PN 16	PN 25	PN 40
10	18	39	39	46	46	46	46
15	22	44	44	51	51	51	51
20	27	54	54	61	61	61	61
25	34	64	64	71	71	71	71
32	43	76	76	82	82	82	82
40	49	86	86	92	92	92	92
50	61	96	96	107	107	107	107
65	77	116	116	127	127	127	127
80	89	132	132	142	142	142	142
100	115	152	152	162	162	168	168
125	141	182	182	192	192	194	194
150	169	207	207	218	218	224	224
200	220	262	262	273	273	284	290
250	273	317	317	328	329	340	352
300	324	373	373	378	384	400	417
350	356	423	423	438	444	457	474
400	407	473	473	489	495	514	546
450	458	528	528	539	555	564	571
500	508	578	578	594	617	624	628
600	610	679	679	695	734	731	747
700	712	784	784	810	804	833	-
800	813	890	890	917	911	942	-
900	915	990	990	1,017	1,011	1,042	-
1,000	1,016	1,090	1,090	1,124	1,128	1,154	-
1,200	1,220	1,290	1,307	1,341	1,342	1,364	-
1,400	1,420	1,490	1,524	1,548	1,542	1,578	-
1,600	1,620	1,700	1,724	1,772	1,764	1,798	-
1,800	1,820	1,900	1,931	1,972	1,964	2,000	-
2,000	2,020	2,100	2,138	2,182	2,168	2,230	-
2,200	2,220	2,307	2,348	2,384	-	-	-
2,400	2,420	2,507	2,558	2,594	-	-	-
2,600	2,620	2,707	2,762	2,794	-	-	-
2,800	2,820	2,924	2,972	3,014	-	-	-
3,000	3,020	3,124	3,172	3,228	-	-	-
3,200	3,220	3,324	3,382	-	-	-	-
3,400	3,420	3,524	3,592	-	-	-	-
3,600	3,620	3,734	3,804	-	-	-	-
3,800	3,820	3,931	-	-	-	-	-
4,000	4,020	4,131	-	-	-	-	-

